


# K45/K65 MOBILE LIGHTING TOWERS

K45 & K65 mobile lighting towers are highly efficient area floodlighting solutions. Made for been used in many environments, headlights can be positioned for 180° to 360° illumination.




 Made in GREAT-BRITAIN

## Technical characteristics

	K45	K65 L3x2	K65 L3x3	K65 L3x4
<b>Electric</b>				
Number of headlights	6	3 x 2	3 x 3	3 x 4
Power supply	650W	730W	1095W	1460W
LED's lifetime	50 000 hours			
Instant power on	Yes			
<b>Security</b>				
Protection index	IP65			
Wind resistance	72 Km/h	50 Km/h	50 Km/h	50 Km/h
Operation temperature range	-15°/+40°			
<b>Photometry</b>				
Color temperature	6 500 °K	5 000° K	5 000° K	5 000° K
Total Lumens	83 000 lm	97 000 lm	146 000 lm	195 000 lm
Dimmable	1% - 100%			
<b>Mechanical</b>				
Closed dimensions (L x W x H)	150 x 40 x 40 cm	109 x 83 x 195 cm	109 x 83 x 195 cm	109 x 83 x 195 cm
Weight	90 Kg	250 Kg	250 Kg	250 Kg
Optimum height for use	4.5 m	6.5 m	6.5 m	6.5 m
Average assembly time	3 minutes			

### Included accessories



#### Adjustable, removable wheel kit

For transport by a single person, storage and security.



#### Independently adjustable legs

Maximum stability when deployed.



#### Fully adjustable headlights

To suit any lighting application including a 360° light pattern.

