

# PREMIUM RANGE

This range is full option with switch ON/OFF 180°/360° and dimmable (3%-100%). Both models are adapted to all applications.



 Made in FRANCE

## Our models



### LUMAPHORE® 300 PREMIUM


45 800 Lumens  
Illuminated area : 2 400 m<sup>2</sup>  
Power : 370 Watts  
IP65 / IK10  
Voltage : 230 Volts  
Weight : 5.4 Kg



### LUMAPHORE® 600 PREMIUM

76 200 Lumens  
Illuminated area : 3 200 m<sup>2</sup>  
Power : 520 Watts  
IP65 / IK10  
Voltage : 230 Volts  
Weight : 8.7 Kg

## Included accessories



### Flight-case

Extremely robust. To transport and protect the LUMAPHORE®.



### Suspension ring

To hang up the LUMAPHORE®.



### 3 switches box

To turn on / turn off the LUMAPHORE®, to vary its intensity and to choose between a 180° or a 360° lighting.

## Technical characteristics

**300 PREMIUM**    **600 PREMIUM**

### Electric

Total lighting output	300W	520W
Power supply	370W	635W
LED's lifetime	50 000 hours	

### Security

Protection index	IP65 / IK10	
Wind resistance	162 Km/h	
Thermal protection	Yes	
Operation temperature range	-15°/+40°	

### Photometry

Illuminated area	2 400 m <sup>2</sup>	3 200 m <sup>2</sup>
Color temperature	5 000° K	
Total Lumens	45 800 lm	76 200 lm
Color rendering index	> 80	
Dimmable	3%-100%	

### Mechanical

Diameter	22.5 cm	
Length	62 cm	91 cm
Weight	5.4 Kg	8.7 Kg
Sleeve type	Diameter 26 mm	
Optimum height for use	4 m	
Average assembly time	2 minutes	

### Standard package

Standard flight-case	Included	
Power cable (Schuko plug)	9,4 m	
Suspension ring	Included	
Sleeve (diam. 26mm)	Included	
IP65 switch (ON/OFF - 180°/360° - dimmable)*	Included	

### Options & accessories

IP67and IP68 Marechal special plug	In option	
4 meters mast	In option	
Different sleeve (diam., DIN, ...)	When ordering	
Magnetic holder	In option	

\*For the 300 PREMIUM, the bottom part of the LUMAPHORE® does not make the 180°/360°.