

XL RANGE COMPACT MODELS

The XL range's LUMAPHORE® are the most appreciated models thanks to their adaptability to all environments. To increase the ground lighting, they are fitted with 4 additional LED's at the lower part.



IP65

IK10

230V

2min

Our models



LUMAPHORE® 300XL


45 800 Lumens
Illuminated area : 2 400 m²
Power : 300 Watts
IP65 / IK10
Voltage : 230 Volts
Weight : 5.1 Kg



LUMAPHORE® 600XL

76 200 Lumens
Illuminated area : 3 200 m²
Power : 520 Watts
IP65 / IK10
Voltage : 230 Volts
Weight : 7.7 Kg

Included accessories



Flight-case

Extremely robust. To transport and protect the LUMAPHORE®.



Suspension ring

To hang up the LUMAPHORE®.

Made in FRANCE

Technical characteristics

300XL **600XL**

Electric

Total lighting output	300W	520W
Power supply	355W	575W
LED's lifetime	50 000 hours	

Security

Protection index	IP65 / IK10	
Wind resistance	162 Km/h	
Thermal protection	Yes	
Operation temperature range	-15°/+40°	

Photometry

Illuminated area	2 400 m ²	3 200 m ²
Color temperature	5 000° K	
Total Lumens	45 800 lm	76 200 lm
Color rendering index	> 80	

Mechanical

Diameter	22,5 cm	22,5 cm
Length	62 cm	91 cm
Weight	5,1 Kg	7,7 Kg
Sleeve type	Diameter 26 mm	
Optimum height for use	4 m	
Average assembly time	2 minutes	

Standard package

Standard flight-case	Included
Power cable (Schuko plug)	7 m
Suspension ring	Included
Sleeve (diam. 26mm)	Included

Options & accessories

IP67and IP68 Marechal special plug	In option
IP65 switch (ON/OFF)	In option
IP65 switch (180°/360°)	In option
IP65 switch (ON/OFF - 180°/360°)	In option
Different sleeve (diam., DIN, ...)	When ordering
4 meters mast	In option
Magnetic holder	In option