

XL RANGE HIGH POWER MODELS

These two models are providing an additional function : an ON/OFF switch and the option for half (180°) or full (360°) illumination. To increase the ground lighting, they are fitted with 8 additional LED's at the lower part.



IP54

IK08

230V

3min

180°

360°

Our models



LUMAPHORE® 1000XL

131 000 Lumens
Illuminated area : 4 500 m²
Power : 890 Watts
IP54 / IK08
Voltage : 230 Volts
Weight : 15.2 Kg



LUMAPHORE® 1500XL

220 800 Lumens
Illuminated area : 6 000 m²
Power : 1 500 Watts
IP54 / IK08
Voltage : 230 Volts
Weight : 17 Kg

Included accessories



Flight-case

Extremely robust. Fitted with two wheels and a handle. To transport and protect the LUMAPHORE®.



2 switches box

To turn on / turn off the LUMAPHORE® and to choose between a 180° or a 360° lighting.

Made in FRANCE

Technical characteristics

1000XL 1500XL

Electric	Total lighting output	890W	1500W
	Power supply	990W	1770W
	LED's lifetime	50 000 hours	
Security	Protection index	IP54 / IK08	
	Wind resistance	110 Km/h	
	Thermal protection	Yes	
	Operation temperature range	-15°/+40°	
Photometry	Illuminated area	4 500 m ²	6 000 m ²
	Color temperature	5 000° K	
	Total Lumens	131 000 lm	220 800 lm
	Color rendering index	> 80	
Mechanical	Diameter	40 cm	
	Length	93 cm	
	Weight	15,2 Kg	17 Kg
	Sleeve type	Diameter 26 mm	
	Optimum height for use	5 m	
	Average assembly time	3 minutes	
Standard package	Standard flight-case	Included	
	Power cable (Schuko plug)	11,4 m	
	IP65 switch (ON/OFF - 180°/360°)	Included	
	Sleeve (diam. 26mm)	Included	
Options & accessories	IP67and IP68 Marechal special plug	In option	
	Different sleeve (diam., DIN, ...)	When ordering	
	5 meters mast	In option	
	Suspension ring	In option	