

XLG RANGE

The XLG range's LUMAPHORE® offer an additional functionality: variation of light intensity. Thanks to a control unit, you can increase or decrease the LUMAPHORE® lighting power. In this range, discover the LUMAPHORE® 1500XLG, the most powerful that delivers 220 800 Lumens.



Made in FRANCE

Our models



LUMAPHORE® 600XLG


76 200 Lumens
Illuminated area : 3 200 m²
Power : 520 Watts
IP65 / IK10
Voltage : 230 Volts
Weight : 8.7 Kg



LUMAPHORE® 1500XLG

220 800 Lumens
Illuminated area : 6 000 m²
Power : 1500 Watts
IP54 / IK08
Voltage : 230 Volts
Weight : 17 Kg

Included accessories



Flight-case

Extremely robust. To transport and protect the LUMAPHORE®.



2 switches box

To turn on / turn off the LUMAPHORE® and to vary its intensity.



Suspension ring

To hang up the LUMAPHORE®. Included only with 600XLG.

Technical characteristics

600XLG **1500XLG**

Electric	Total lighting output	520W	1500W	
	Power supply	635W	1770W	
	LED's lifetime	50 000 hours		
Security	Protection index	IP65 / IK10	IP54 / IK08	
	Wind resistance	162 Km/h	110 Km/h	
	Thermal protection	Yes		
	Operation temperature range	-15°/+40°		
Photometry	Illuminated area	3 200 m ²	6 000 m ²	
	Color temperature	5 000° K		
	Total Lumens	76 200 lm	220 800 lm	
	Color rendering index	> 80		
	Dimmable	3%-100%		
	Mechanical	Diameter	22,5 cm	40 cm
Length		91 cm	93 cm	
Weight		8,7 Kg	17 Kg	
Sleeve type		Diameter 26 mm		
Optimum height for use		4 m	5 m	
Average assembly time		2 minutes	3 minutes	
Standard package		Standard flight-case	Included	
		Power cable (Schuko plug)	9,4 m	11,4 m
	Suspension ring	Included	When ordering	
	IP65 switch (ON/OFF - dimmable)	Included		
Options & accessories	Sleeve (diam. 26mm)	Included		
	IP67and IP68 Marechal special plug	In option		
	Different sleeve (diam., DIN, ...)	When ordering		
	4 meters mast	In option		
	Magnetic holder	In option	-	