

MINILITE®

Delivered in a TITAN KIT with a mast in a flight-case, the MINILITE® is easy to move and set up. It's ideal for indoor or finishing work.



IP44

230V

2min

360°

Our models



MINILITE@100L

8 120 Lumens
Illuminated area : 300 m²
Power : 70 Watts
IP44
Voltage : 230 Volts
Weight : 3.5 Kg



MINILITE@100XL

12 000 Lumens
Illuminated area : 350 m²
Power : 90 Watts
IP44
Voltage : 230 Volts
Weight : 3.6 Kg

Included accessories



Flight-case

To transport and protect the MINILITE® and its mast.



Mast

To fix and place the MINILITE® to an optimum height for use.



Suspension ring

To hang up the MINILITE®.

Made in FRANCE

Technical characteristics

	100L	100XL	
Electric	Total lighting output	70W	90W
	Power supply	75W	95W
	LED's lifetime	50 000 hours	
Security	Protection index	IP44	
	Operation temperature range	-15°/+40°	
Photometry	Illuminated area	300 m ²	350 m ²
	Color temperature	4 700° - 5 000° K	
	Total Lumens	8 120 lm	12 000 lm
	Color rendering index	> 80	
Mechanical	Diameter	22,5 cm	
	Length	55 cm	
	Weight	3,5 Kg	3,6 Kg
	Sleeve type	Diameter 26 mm	
	Optimum height for use	2 to 4 m	
	Average assembly time	2 minutes	
	Standard package	Standard flight-case	Included
Power cable (Schuko plug)		7 m	
Suspension ring		Included	
Sleeve (diam. 26mm)		Included	
1.80 meters mast		Included	
Options & accessories	IP67and IP68 Marechal special plug	In option	
	IP65 switch (ON/OFF)	When ordering	
	4 meters mast	In option	
	Different sleeve (diam., DIN, ...)	When ordering	
	Magnetic holder	In option	